



RACKview SERIES

Rack Mount Monitor

Hinged for Easy Access and Space Preservation

Rugged, Steel Front Bezel

12.1", 15" & 17" LCD Display Sizes

Optional Touch Screen

On-screen Display Menu Lockout Feature

Maximized space with enhanced, rugged usability!



thinENGINEcomputer

RACKview SPECIFICATIONS

Enclosure

- Sealed rugged cast aluminum enclosure, adheres to NEMA 4X
- Tough, black powder coat paint

Display

- Resolution
 - 12.1" LCD: SVGA - 800x600 - 400 NIT
 - 15.0" LCD: XVGA - 1024x768 - 300 NIT
 - 17.0" LCD: SXGA - 1280x1024 - 300 NIT
- Optional anti-reflective/anti-glare or heat-reflective filming

Touchscreen

- Optional: Resistive Analog Touch Screen
- Optional: 3M Capacitive Touch, Serial or USB
- Optional: Infra Red Touch, Serial or USB

Power

- External Power Supply, 12V
- 6-foot power cord

Environmental & Rugged

- Operation : -0°C ~ 50°C, 32°F ~ 122°F
- Storage : -20°C ~ 60°C, -4°F ~ 140°F
- Operating Shock : 10g, 11ms, 1/2 sine
- Operating Vibration: .41g, 3-500 Hz
- Adheres to NEMA 4X Specifications

Video Interface

- VGA or component

Dimensions and Weight

- RACKview™ 120: 9.0 lbs
10.470" (H) x 19.000" (W) x 2.375" (D)
- RACKview™ 150: 12.0 lbs
12.220" (H) x 19.000" (W) x 2.375" (D)
- RACKview™ 170: 14.5 lbs
13.970" (H) x 18.970" (W) x 2.25" (D)

Standard Package

- RACKview Main Unit
- External power supply with cable



OSD

- Easy-access on-screen display panel



Slim Design

- Side look of the unit



Power Supply

- External power supply